


WOOL STYLE

RADICI
CARPET

CE EN14041



Specifications and tolerances in according EN 1307



STAINADVERSE



CONSTRUZIONE	CONSTRUCTION	TECHNIQUE DE FABRICATION	HERSTELLUNGSVERFAHREN
TUFTING RICCIO STAMPATO 5/32"	TUFTED LOOP PILE PRINTED 5/32"	TUFTED BOUCLÉ IMPRIMÉ 5/32"	GETUFTED BEDRUCKTER SCHLINGE 5/32"
COMPOSIZIONE	COMPOSITION	COMPOSITION	POLNUTZSCHICHT
100% LANA	100% WOOL	100% LAINE	100% WOLLE
SOTTOFONDO	SECONDARY BACKING	DOSSIER	RÜCKENAUSRÜSTUNG
JUTA SINTETICA	SYNTHETIC JUTE	JUTE SYNTHÉTIQUE	SDR TEXTILRUCKEN
PUNTI AL M ²	STITCHES PER M ²	TOUFFES AU M ²	KNOTEN M ²
± 90000	± 90000	± 90000	± 90000
ALTEZZA PELO	PILE HEIGHT	HAUTEUR DU VELOURS	POLHÖHE
± 3.8 mm	± 3.8 mm	± 3.8 mm	± 3.8 mm
ALTEZZA TOTALE	TOTAL HEIGHT	HAUTEUR TOTALE	GESAMTHÖHE
± 7.5 mm	± 7.5 mm	± 7.5 mm	± 7.5 mm
PESO FIBRA	YARN WEIGHT	POIDS DU VELOURS	POLGEWICHT
± 1000 g/m ²	± 1000 g/m ²	± 1000 g/m ²	± 1000 g/m ²
PESO TOTALE	TOTAL WEIGHT	POIDS TOTAL	GESAMTGEWICHT
± 2150 g/m ²	± 2150 g/m ²	± 2150 g/m ²	± 2150 g/m ²
LARGHEZZA ROTOLO	ROLL WIDTH	LARGEUR DU ROLEAU	BREITE
400 cm	400 cm	400 cm	400 cm
FAMIGLIA TUFTING 21	FAMIGLIA TUFTING 21	FAMIGLIA TUFTING 21	FAMIGLIA TUFTING 21



COMFORT: ★★★★★

BUSINESS WEARABILITY: ★★★

DOMESTIC WEARABILITY: ★★★

Colour fastness to light	≥ 5 (4 Pastel shade)	Thermal resistance m ² K/W	≤ 0,17
Insulation impact noise ΔLw	25 dB	Body voltage walking test kV	≤ 2
Acoustical absorption α _w	0,15		