

# BLOOM 1000

**RADICI**  
CARPET

CE EN14041



Specifications and tolerances in according EN 1307

**ECONYL®**



Information sur le niveau d'émission de substances volatiles dans l'air intérieur, présentant un risque de toxicité par inhalation, sur une échelle de classe allant de A+ (très faibles émissions) à C (fortes émissions)

**STAINADVERSE**



CONSTRUZIONE	CONSTRUCTION	TECHNIQUE DE FABRICATION	HERSTELLUNGSVERFAHREN
TUFTING VELLUTO STAMPATO 1/10"	TUFTED CUT PILE PRINT 1/10"	TUFTED VELOURS IMPRIMÉ 1/10"	GETUFTED DRUCKVELOURS 1/10"
COMPOSIZIONE	COMPOSITION	COMPOSITION	POLNUTZSCHICHT
100% POLIAMMIDE 6-ECONYL	100% POLYAMIDE 6-ECONYL	100% POLYAMIDE 6-ECONYL	100% POLYAMID 6-ECONYL
SOTTOFONDO	SECONDARY BACKING	DOSSIER	RÜCKENAUSRÜSTUNG
JUTA SINTETICA	SYNTHETIC JUTE	JUTE SYNTHÉTIQUE	SDR TEXTILRUCKEN
PUNTI AL M <sup>2</sup>	STITCHES PER M <sup>2</sup>	TOUFFES AU M <sup>2</sup>	KNOTEN M <sup>2</sup>
± 209350	± 209350	± 209350	± 209350
ALTEZZA PELO	PILE HEIGHT	HAUTEUR DU VELOURS	POLHÖHE
± 5.5 mm	± 5.5 mm	± 5.5 mm	± 5.5 mm
ALTEZZA TOTALE	TOTAL HEIGHT	HAUTEUR TOTALE	GESAMTHÖHE
± 8.0 mm	± 8.0 mm	± 8.0 mm	± 8.0 mm
PESO FIBRA	YARN WEIGHT	POIDS DU VELOURS	POLGEWICHT
± 1000 g/m <sup>2</sup>	± 1000 g/m <sup>2</sup>	± 1000 g/m <sup>2</sup>	± 1000 g/m <sup>2</sup>
PESO TOTALE	TOTAL WEIGHT	POIDS TOTAL	GESAMTGEWICHT
± 2000 g/m <sup>2</sup>	± 2000 g/m <sup>2</sup>	± 2000 g/m <sup>2</sup>	± 2000 g/m <sup>2</sup>
LARGHEZZA ROTOLO	ROLL WIDTH	LARGEUR DU ROLEAU	BREITE
400 cm	400 cm	400 cm	400 cm
FAMIGLIA TUFTING 1	FAMIGLIA TUFTING 1	FAMIGLIA TUFTING 1	FAMIGLIA TUFTING 1



**COMFORT:** ★★★★★

**BUSINESS WEARABILITY:** ★★★

**DOMESTIC WEARABILITY:** ★★★

This product is recyclable. For more information, please contact us at [info@radicicarpet.it](mailto:info@radicicarpet.it)

Colour fastness to light	≥ 5	Thermal resistance m2 K/W	≤ 0,17
Insulation impact noise ΔLw	27 dB	Body voltage walking test kV	≤ 2
Acoustical absorption α <sub>w</sub>	0,20		