


AMBIENTE


ECONYL®

STAINADVERSE


COSTRUZIONE	CONSTRUCTION	TECHNIQUE DE FABRICATION	HERSTELLUNGSVERFAHREN
TUFTING RICCIO EFFETTO TONO 1/10"	TUFTED LOOP PILE TONAL EFFECT 1/10"	TUFTED BOUCLÉ À EFFET DE COULEUR 1/10"	GETUFTED SCHLINGE MEHRFARBIG UNGEMUSTERT 1/10"
COMPOSIZIONE	COMPOSITION	COMPOSITION	POLNUTZSCHICHT
100% POLIAMMIDE 6-ECONYL	100% POLYAMID 6-ECONYL	100% POLYAMIDE 6-ECONYL	100% POLYAMID 6-ECONYL
SOTTOFONDO	SECONDARY BACKING	DOSSIER	RÜCKENAUSRÜSTUNG
JUTA SINTETICA	SYNTHETIC JUTE	JUTE SYNTHÉTIQUE	SDR TEXTILRUCKEN
PUNTI AL M ²	STITCHES PER M ²	TOUFFES AU M ²	KNOTEN M ²
± 90850	± 90850	± 90850	± 90850
ALTEZZA PELO	PILE HEIGHT	HAUTEUR DU VELOURS	POLHÖHE
± 4.4 mm	± 4.4 mm	± 4.4 mm	± 4.4 mm
ALTEZZA TOTALE	TOTAL HEIGHT	HAUTEUR TOTALE	GESAMTHÖHE
± 7.2 mm	± 7.2 mm	± 7.2 mm	± 7.2 mm
PESO FIBRA	YARN WEIGHT	POIDS DU VELOURS	POLGEWICHT
± 700 g/m ²	± 700 g/m ²	± 700 g/m ²	± 700 g/m ²
PESO TOTALE	TOTAL WEIGHT	POIDS TOTAL	GESAMTGEWICHT
± 1900 g/m ²	± 1900 g/m ²	± 1900 g/m ²	± 1900 g/m ²
LARGHEZZA ROTOLO	ROLL WIDTH	LARGEUR DU ROLEAU	BREITE
400 cm	400 cm	400 cm	400 cm
FAMIGLIA TUFTING 3	FAMIGLIA TUFTING 3	FAMIGLIA TUFTING 3	FAMIGLIA TUFTING 3


COMFORT: ★★☆☆☆
BUSINESS WEARABILITY: ★★☆☆
DOMESTIC WEARABILITY: ★★☆☆

Colour fastness to light	≥ 5	Thermal resistance m2 K/W	≤ 0,17
Insulation impact noise ΔLw	25 dB	Body voltage walking test kV	≤ 2
Acoustical absorption α _w	0,15		

This product is recyclable. For more information, please contact us at info@radicarpet.it

Radici Pietro Industries & Brands Spa - 24026 Cazzano Sant'Andrea (BG) Italia - www.radicarpet.it - info@radicarpet.it

Radici Pietro I&B. reserves the right to modify the characteristics of the product while keeping the same technical properties

TSO1/2025