


FUNKY

RADICI
CARPET



COSTRUZIONE	CONSTRUCTION	TECHNIQUE DE FABRICATION	HERSTELLUNGSVERFAHREN
TUFTING RICCIO EFFETTO TONI DI COLORE 1/10"	TUFTED LOOP PILE TONAL EFFECT 1/10"	TUFTED BOUCLÉ À EFFET DE COULEUR 1/10"	GETUFTED SCHLINGE MEHRFARBIG UNGEMUSTERT 1/10"
COMPOSIZIONE	COMPOSITION	COMPOSITION	POLNUTZSCHICHT
100% NYLON SOLUTION DYED	100% NYLON SOLUTION DYED	100% NYLON SOLUTION DYED	100% NYLON SOLUTION DYED
SOTTOFONDO	SECONDARY BACKING	DOSSIER	RÜCKENAUSRÜSTUNG
JUTA SINTETICA	SYNTHETIC JUTE	JUTE SYNTHÉTIQUE	SDR TEXTILRUCKEN
PUNTI AL M ²	STITCHES PER M ²	TOUFFES AU M ²	KNOTEN M ²
± 189600	± 189600	± 189600	± 189600
ALTEZZA PELO	PILE HEIGHT	HAUTEUR DU VELOURS	POLHÖHE
± 2.9 mm	± 2.9 mm	± 2.9 mm	± 2.9 mm
ALTEZZA TOTALE	TOTAL HEIGHT	HAUTEUR TOTALE	GESAMTHÖHE
± 5.1 mm	± 5.1 mm	± 5.1 mm	± 5.1 mm
PESO FIBRA	YARN WEIGHT	POIDS DU VELOURS	POLGEWICHT
± 520 g/m ²	± 520 g/m ²	± 520 g/m ²	± 520 g/m ²
PESO TOTALE	TOTAL WEIGHT	POIDS TOTAL	GESAMTGEWICHT
± 1630 g/m ²	± 1630 g/m ²	± 1630 g/m ²	± 1630 g/m ²
LARGHEZZA ROTOLO	ROLL WIDTH	LARGEUR DU ROLEAU	BREITE
400 cm	400 cm	400 cm	400 cm
FAMIGLIA TUFTING 3	FAMIGLIA TUFTING 3	FAMIGLIA TUFTING 3	FAMIGLIA TUFTING 3



COMFORT: ★★☆☆☆

BUSINESS WEARABILITY: ★★★★★

DOMESTIC WEARABILITY: ★★★★★

Colour fastness to light	≥ 5	Thermal resistance m2 K/W	≤ 17
Insulation impact noise ΔLw	25 dB	Body voltage walking test kV	≤ 2
Acoustical absorption α _w	0,15		

This product is recyclable. For more information, please contact us at info@radicicarpet.it

Radici Pietro Industries & Brands Spa - 24026 Cazzano Sant'Andrea (BG) Italia - www.radicicarpet.it - info@radicicarpet.it

Radici Pietro I&B. reserves the right to modify the characteristics of the product while keeping the same technical properties

TSO1/2025